



YOUR NO 1 TRADE SHOP
COLOREX
TRADE & HIRE

Tradies Easy Sand Sealer

Description:

Tradies Easy Sand Sealer is an acrylic paint designed for application by air less spray gun. Easy Sand has excellent opacity, adhesion, sealing, filling and flow and as the name suggests it's easy to sand to a smooth finish in preparation for the finish coats. It is suitable for interior areas, particularly new walls and ceilings.

Physical Properties

Resin Type:	Modified Acrylic
Solvent:	Water
Colour:	White
Finish:	Matt
Drying time:	2 hours @18c
Recoat time:	2 hours @18c
Dry Film Thickness:	35µ depending on requirement and application
No. of coats:	1 -
Theoretical Coverage:	10/12m ² /litre depending on application
Primer Needed:	No
Thinning & Cleaning:	Recommended. Use water
V.O.C.	22 G/L

Performance:

- Good adhesion to pine, MDF and stopping and finishing compounds.
- Excellent sanding properties
- Extremely high opacity
- Excellent adhesion
- Recoatable with all systems
- Water based

Limitations:

- Not to be used over aged plasterboard or wall reinstatement after wall paper removal.
- Not recommended for exterior use.
- All preparation and painting must conform to AS2311: The Painting of Buildings.
- Do not overspread or exceed 12.0 square metres per litre per coat. In hot weather, rinse brush every half hour or use two and keep one standing in water.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Commercial Coating Manufacturers Ltd makes no representation as to the completeness and accuracy thereof.

In no event will Commercial Coating Manufacturers Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.

- Do not apply if temperature is under 10C, or when temperature of surface may fall below 10C during the drying period, otherwise film formation will not be complete and a fall-off in properties will result.

Substrate Preparation:

- Ensure all surfaces are clean, dry and dust free.
- Apply 1 full coat of **Tradies Easy Sand Sealer** to new plasterboard, fibrous plaster, MDF and pine.
- For old and yellowed plasterboard and painted surfaces use Paint Tech **All-Prime** as the first coat or **Tradies Alkyd Pigmented Sealer Undercoat**.

Application:

Tradies Easy Sand Sealer may be applied by brush, roller or spray. Do not thin more than 10% as necessary for application method. Clean up with water.

NB:

- Avoid breathing sanding dust. Usage of dust mask is recommended.
- Sealing of **Tradies Easy Sand** in wet areas and before finishing with water based enamels is recommended.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Commercial Coating Manufacturers Ltd makes no representation as to the completeness and accuracy thereof.

In no event will Commercial Coating Manufacturers Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.